

Exploring the New World of Neutrino Physics

Rob Plunkett
Fermilab Academic Lecture Series
Section III - Spring 2006

Lecture 1 - Beams, decays, and signals of oscillation



What this Course is about

- Concentrate on specific examples of current and future oscillation physics.
- Discuss them in the context of general principles which unify them.
- Occasional "sidebars" for interest.
- Focus on things going on at Fermilab or with lab participation.
- Understand limitations and fundamental systematics.
- Discuss future neutrino sources needed for precision work.



What this Course is NOT about

- Not a general review of all neutrino physics, or even all oscillations,
- Not a detailed quantitative comparison of various proposed or running experiments
- No discussion of lots of interesting areas
 - Solar neutrinos
 - Purely atmospheric experiments (except in passing)
 - Double beta-decay
 - Astrophysical neutrinos



Basics of Neutrino Oscillation Experiments

As in all neutrino experiments, basically <u>counting</u> experiments.

(1) Secondary particle creation

e.g.
$$pN \to n\pi^{\pm} + X$$
 Model Uncertainties

(2) Decay and projection of secondaries

e.g.
$$\pi^+ \to \mu^+ \nu_{\mu}$$
 Understood.

(3) Oscillation or new physics

$$V_{\alpha} \rightarrow V_{\beta}$$
 To be measured

(4) Interactions in detector

$$\begin{array}{ll} \text{Charged Current (CC)} & \nu_{\alpha} N \longrightarrow \ell_{\alpha} X & \text{Model} \\ \text{Neutral Current (NC)} & \nu_{\alpha} N \longrightarrow \nu_{\alpha} X & \text{Uncertainties} \end{array}$$

(5) Measurement in detector

Usual problems



Refinements on the Basic Idea

May sub-divide counting by categories

- Type of lepton in CC, μ, e, τ
- Kinematic variables:

e.g
$$E_{\nu}$$
, $y = E_{hadrons}/E_{\nu}$

Basic measurement is

$$N = arphi_{\scriptscriptstyle V}(E_{\scriptscriptstyle V})\,\sigma_{\scriptscriptstyle V}(E_{\scriptscriptstyle V})$$
 cross-section of interest


Must deconvolute using inference, simulation, previous data, and ratios

<u>Sidebar-Neutrino</u> <u>Oscillations - Optical Analogy</u>


Birefringent crystal - different index of refraction (light speed) for different polarizations

Polarization rotates because of differential

phase advance



 $R = \frac{e^{ik_1 x}}{e^{ik_2 x}}$




For neutrinos

$$k = \frac{\omega}{c} n = \frac{\omega}{c} \beta$$


$$m\gamma = E_V$$


giving

$$R = e^{i\Delta k x} = e^{i\frac{m_1^2 - m_2^2}{2E}x}$$



Oscillation as "Flavor Polarization" Rotation





In general case, rotation isn't complete

$$P(\nu_{\mu}^{2}) = 1 - \sin^{2}(2\theta)\sin^{2}(\frac{\Delta k x}{2})$$



Categorize experiments as appearance or disappearance

Disappearance - look for a loss of v flux as a function of spectrum.

Typical $v_{\mu} \rightarrow v_{x}$, where x = e, τ does not leave typical CC muon in the detector.

Flux, spectral knowledge important systematics.

Examples: MINOS, reactor v_e experiments

Appearance - look for the presence of types of v's that shouldn't be there.

Here we are finding the v_x end product of oscillation directly.

Backgrounds now a major systematic!

Examples: NOvA, CNGS, MiniBoone



Two detectors improves control of oscillation measurements

We need to measure P_{osc} , the survival or appearance probability, but what we see is

$$N_{obs}^{far} = (\varphi_v \, \sigma_v)_{far}^{true} P_{osc}$$

With the extra measurement at a near detector we can form

$$(\varphi_{v}\sigma_{v})_{far}^{true} = (\varphi_{v}\sigma_{v})_{near}^{meas} \frac{(\varphi_{v})_{far}^{MC}}{(\varphi_{v})_{near}^{MC}}$$
Our measurement at the pear

Our measurement at the near

Well-controlled systematics on this ratio



2-v Oscillations in a

3-v World

General "Euler Rotation" **Formalism**

$$\begin{pmatrix} v_e \\ v_\mu \\ v_\tau \end{pmatrix} = U \begin{pmatrix} v_1 \\ v_2 \\ v_3 \end{pmatrix}$$

$$\begin{aligned} &U = U_{23}U_{13}U_{12} \\ &= \begin{pmatrix} 1 & 0 & 0 \\ 0 & c_{23} & s_{23} \\ 0 & -s_{23} & s_{23} \end{pmatrix} \begin{pmatrix} c_{13} & 0 & s_{13}e^{i\delta} \\ 0 & 1 & 0 \\ -s_{13}e^{-i\delta} & 0 & c_{13} \end{pmatrix} \begin{pmatrix} c_{12} & s_{12} & 0 \\ -s_{12} & c_{12} & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

gives

$$P_{
u_{\mu} o
u_{\tau}} \propto 4 (U_{\mu_{1}} U_{\tau_{1}} U_{\mu_{3}} U_{\tau_{3}} + U_{\mu_{2}} U_{\tau_{2}} U_{\mu_{3}} U_{\tau_{3}})$$
 and

and

$$P_{\nu_{\mu} \to \nu_{\tau}} = \cos^4 \theta_{13} \sin^2 2\theta_{23} \sin^2 (\Delta_{13})$$

Ignoring solar oscillations,

Familiar 2-generation formula

Note nula
$$\Delta_{13}=1.27\Delta m_{13}^2L/E_{_{12}}$$

Beam Transport and Secondary Focusing

- Every conventional neutrino experiment starts by focusing a proton beam on a target
- Beamline elements are bending magnets (dipoles) and lenses (quadrupoles and sextapoles)
- There are a variety of ways to focus the secondary particles created in the target, which make neutrinos.
 - Horn focusing
 - Quad focusing
- Will discuss the target physics separately




Primary Focusing - Magnetic Quadrupole Lenses


As with all magnets

$$P_T = \int B \, dl$$

In a quadrupole magnet, field strength increases linearly with distance from axis, forming a lens.




Maxwell's equations insist that focussing in x must be defocusing in y. (Field direction)





Magnetic Field in a Quadrupole Magnet



Unlike an optical lens, only focuses one plane. If the magnet is rotated, it couples motion in the two planes.

There is an analytic formalism to understand this.


Picture from Feynman Lectures on Physics



Transfer Matrix Formalism

$$\begin{pmatrix} y \\ y' \end{pmatrix} = \begin{pmatrix} position \\ angle \end{pmatrix}$$

focusing from minus



$$\begin{pmatrix}
1 & 0 \\
1/f & 1
\end{pmatrix}
\begin{pmatrix}
y \\
0
\end{pmatrix} = \begin{pmatrix}
y \\
y/f
\end{pmatrix}$$
defocusing



"FODO" Cell to focus both

planes


$$= \begin{pmatrix} y - \ell y / f \\ -\ell y / f^2 \end{pmatrix}$$

focusing if $\ell < f$,

goes like distance from axis


$$\begin{pmatrix} 1 & 0 \\ -1/f & 1 \end{pmatrix} \begin{pmatrix} 1 & \ell \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ 1/f & 1 \end{pmatrix}$$


Other plane also focussing





Real Elements of NuMI Beamline






NuMI Pretarget final transport



NuMI Target - where the decaying particles start





60 cm graphite fins - water cooled Be windows at either end

Absorbs 40 KW of power at design intensities.


Careful modeling because distribution of particles coming out affects v flux

Sidebar- advanced targeting

At very high beam powers, targeting becomes more difficult.

Radiation, heat transfer, shock issues.


SNS flowing liquid mercury target absorbs 2 MW!





Neutrino intensity depends on beam power

Counter-intuitive because fewer incident particles!



As primary beam energy increases, more low x particles are brought within the focussing zone



Secondary Particle Production

 π and K production in the target are the ultimate source of neutrino flux

Knowledge and understanding of this is an important systematic for oscillation experiments.

Two types of modeling (using experimental data as input):

-Hadronic cascade Monte Carlos

FLUKA, MARS, GEANT


Tend to be "black boxes" Hard to factorize errors

Parametrized Simulations

Example for these lectures: BMPT Provide the experimenter with functions, errors



Experimental data compared to NuMI data range



Notes: in parametrizations, data may use scaling variables

$$x_F \equiv 2p_L^* / \sqrt{s}$$

These two especially especially are the second and the second are the se


These two very similar, especially for π 's

$$x_{lab} \equiv p_{lab} / p_{incident}$$



Example of BMPT parametrization - K's

Invariant cross-section under $p_L --> \gamma p_L$



BMPT parametrization


$$E\frac{d^{3}\sigma}{d^{3}p} = A(1-x_{R})^{\alpha} x_{R}^{-\beta} G(x_{R}, p_{T}) e^{-a(x_{R})p_{T}}$$

Notes: Limited p_T!

Cutoff at high x

Enhancement at low x


Example of experimental program- MIPP experiment at Fermilab



Study p,K + A interactions from 5-85 GeV Study p + A interactions at 120 GeV Measurements on H, Be, C, various metals

Typical MIPP Preliminary Data

MIPP



Inclusive x_F distributions for Be (top) and C (bottom) targets


Working through target list including NuMI target

Coutesy Messier, NOVE-06



Example of Secondary Focusing: Parabolic Horn

Old technology - form pulsed sheets of current in a cylindrical geometry. $I \propto r^2$



Many variations on this shape have been made, with different momentum acceptances

HIGH CURRENTS - e.g. NuMI horn uses 180 kA for ~2 mS.

NuMI horn under construction Outer Conductor Stripline

Horn 2 inner conductors



Prototype horn 1 in test stand







Secondary Beam Monitoring









Scan of beam across target shows edges, increased production in outer baffle - real detail!



Neutrinos from π, K Decay -Spectrum

Two-body decay $\pi \rightarrow \mu \nu$ of CM energy E*

Lorenz Transformation of P_I, E

$$M = \gamma (1 + \beta \cos \theta^*)$$

$$M \cos \theta = \gamma (\cos \theta^* + \beta)$$

$$using$$

$$M \equiv E_{lab} / E^*$$

$$M = \frac{1}{\gamma(1 - \beta\cos\theta)}$$

$$\approx \frac{1}{\gamma(1 - \cos\theta)} \approx \frac{2\gamma}{1 + \gamma^2\theta^2}$$

Spectrum depends on angle Sharper for increased π energy

Neutrinos from π , K Decay - Flux

Lorenz transform P_T this time

$$E \sin \theta = E^* \sin \theta^*$$

$$M \sin \theta = \sin \theta^*$$

for small angles

$$\sin \theta \cong \theta \Rightarrow M\theta = \theta^*$$


$$\Rightarrow \frac{d\theta^*}{d\theta} = M$$
actually, this is valid for all values of θ^*

giving flux compression factor

$$\frac{d\Omega^*}{d\Omega} = \frac{\sin \theta^* d\theta^*}{\sin \theta d\theta} = M^2 = \frac{4\gamma^2}{(1+\gamma^2 \theta^2)^2}$$




NuMI Beamline Layout



120 GeV primary Main Injector beam Target readily movable in beam direction 2-horn beam adjusts for variable energy ranges 675 meter decay pipe for π decay

类

Beam Energy Variability



v_{μ} CC Events in MINOS 5kt detector (2.5 x 10^{20} POT/yr)


Low $\sim 1600/\text{yr}$

Medium ~ 4300/yr

High ~ 9250/yr




Neutrino Beam 101 (from Sacha Kopp)






Beamline Flux Fractional Uncertainties in NuMI Beam



Does not include errors from hadron production model




Study typical uncertainties with beam energy evolution



NuMI high energy beam at near location (inset repeats the low energy plot)



Spread of a neutrino spectrum due to parent hadron uncertainties



Spread due to models: 8% (peak)

15% (tail)


 $ν_{\mu}$ Energy [GeV]

Kopp, et. al.




Two detectors to reduce uncertainty

Examples from MINOS simulations using FLUKA





Interlude - the physics of 0.5-5 GeV Neutrino Interactions



Complex physics modeled as a combination of low-multiplicity processes



Pions are produced via intermediate resonant states





Fig. 4.6 Variation of total cross section for π^+ and π^- mesons on protons, with incident pion energy. The symbol Δ refers to resonances of $I=\frac{3}{2}$; N refers to $I=\frac{1}{2}$. The positions of only a few of the known states, together with their spin-parity assignments, are given.

Resonances as observed in π n scattering experiments (Figure from Perkins, Introduction to High Energy Physics


<u>Different models have</u> underlying physics in common




 v_l v_l

Quasi-elastic

Resonant π production





Coherent production


DIS


Different models combine channels differently.


e.g. NUANCE - coherent addition of resonances NEUGEN - incoherent addition



Existing data not strongly constraining








Coherent, v-bar data basically nonexistent in region of interest.



Parameters in the models are tuned to exclusive channel cross sections.

$$\sigma_{tot} = \sigma_{QE} + \sum_{i} (\sigma_{res}^{i} + f_{i}\sigma_{DIS}^{i})$$

Charged Current Single Pion Production



Examples from NEUGEN courtesy H. Gallagher

10

E, (GeV)


10

E, (GeV)




<u>Worldwide effort to improve</u>

<u>knowledge</u>




MiniBoone single π (Monroe, Wasco)

Plots courtesy G. Zeller, NOvE-06



MINERvA, a fine-grained neutrino scattering experiment







- Precision study of ν nucleus scattering.
- ◆Important for minimizing systematic errors of neutrino oscillation experiments
- ◆To be located just upstream of MINOS Near Near Detector
- ♦High-granularity, fully-active (~6T) scintillator strip based design.
- ◆~1 T of nuclear targets (C,Fe,Pb) form first detector section.

Example of MINERvA's Analysis Potential Coherent Pion Production

CC Coherent Pion Production Cross Section



Some points are NC data rescaled to CC





MINOS Long-Baseline <u>Experiment</u>



Fermilab to Soudan, Minnesota

Near Detector: 980 tons

Fermilab


10 km

730 km

km



Two-detector Disappearance Experiment




Study atmospheric scale

 $V_{\mu} \rightarrow V_{\tau} \Delta m^2 \text{ and } \sin^2 2\theta_{23}$ Greatly improve existing measurement;

excellent test against alternative hypotheses

Sensitivity to v_e appearance discussed later



The MINOS Far Detector



8m Octagonal Tracking Calorimeter

486 layers of 2.54cm magnetized Fe plates 2 sections, each 15m long


4.1cm wide solid scintillator strips with WLS fiber readout (both ends).

Hamamatsu M16 multi-anode PMT readout

Veto shield against entering cosmic ray muons



Detector Technology



See talks by A. Pla-Dalmau, J. Grudzinski for more details.

Scintillator strips are extruded polystyrene (Itasca Plastic)


1.2 mm Kuraray wavelength shifting fiber fits into groove

Groups of 20 or 28 strips are assembled into "modules"

Both ends read out to increase light yield.


类


MINOS Detector Technology



MINOS Calibration Detector








60-plane 'micro - MINOS' Also checked near/far electronics



MINOS Near Detector - slightly different



280 single steel plates, shorter modules

Calorimeter (1st 3/7 - logically Veto, Target, Hadron Absorber is partially instrumented except for 1/5 of planes with full coverage

Muon Spectrometer section has only every 5th plane instrumented

Magnet coil provides ~ 1.3 T

Near electronics optimized for high occupancy (~20) during 10 µs spill